



X-CUBE COMPACT

TOP PERFORMANCE, SMALL SIZE - COMPACT. **EFFICIENT. TROX**

The X-CUBE compact distinguishes itself by high quality in each and every detail

and a whole spectrum of intelligent advantages

With the X-CUBE compact TROX has created a ready-to-operate and preconfigured air handling unit that combines the excellent features of the X-CUBE in the smallest of spaces. These units handle volume flow rates of 600 to 6,000 m³/h and offer a heat recovery efficiency of over 80 % (dry, to EN 308), hence they are the ideal solution for small and midrange applications.

Energy-efficient plug fans with EC motor ensure maximum efficiency and low sound power levels.

An extensive range of accessories, such as a heating coil, a CO2 sensor

and a room control panel, can easily be connected to the X-CUBE control system.

Advantages at a glance

- Volume flow rates of 600 to 6,000 m³/h

- Maximum energy efficiency
 Powerful EC fans
 High level of hygiene (conforms to VDI 6022)
 Heat recovery with rotary heat exchanger or counter flow plate heat exchanger
- Air filtration with TROX minipleat or NanoWave filters
- Ready-to-operate unit (plug and play)
- Integral, bus compatible controls
- Intuitive operation
- Integration with advanced ventilation and air conditioning systems
- Optional weatherproof version with powder-coated metal roof to protect the unit and accessories, with perimeter drip edge, RAL 7012
- Made in Germany



DUR X-CUBE

 \cap NITACT