



POCKET FILTER, TYPE  
PFS



TESTED TO VDI 6022

Tested to VDI 6022

## TYPE PFS

[Configure now](#)

### PREFILTERS OR FINAL FILTERS IN VENTILATION SYSTEMS

Pocket filters for the separation of fine dust

- Filter groups ISO ePM10, ISO ePM2.5 and ISO ePM1 (fine dust filters)
- Performance tested to ISO 16890
- Eurovent certification for fine dust filters
- Meets the hygiene requirements of VDI 6022
- Non-woven synthetic fibres, welded
- Enlarged filter area due to filter pockets
- Low initial differential pressure and high dust holding capacity
- Different numbers of pockets and pocket depths
- Quick installation and filter changing times due to easy, safe handling
- Fitting into standard cell frames for filter walls (type SIF) or into universal casings (type UCA) for duct installation

Optional equipment and accessories

- Front frame made of plastic or galvanised sheet steel

## Application

### Application

- Pocket filter made of non-woven synthetic fibres type PFS for the separation of fine dust
- Fine dust filter: Prefilter or final filter in ventilation systems

### Nominal sizes

- B × H × T [mm]

## Description

### Construction features

- Frame depth of construction PLA: 25 mm
- Frame depth of construction GAL: 20, 25 mm
- Number of pockets: 3, 4, 5, 6, 7, 8

### Materials and surfaces

- Filter media made of non-woven synthetic fibres
- Frame made of plastic or galvanised sheet steel

### Standards and guidelines

- Test according to ISO 16890; international standard for general room air distribution; classification of arrestance efficiency based on the measured fractional arrestance efficiency, which is processed into a reporting system for the fine dust arrestance efficiency (ePM)
- For fine dust filters, the fractional arrestance efficiency of a certain size range is determined by aerosols (DEHS and KCl)
- The filters are classified into filter groups ISO ePM10, ISO ePM2.5 and ISO ePM1 depending on the tested values
- Construction PLA meets the hygiene requirements of VDI 6022, VDI 3803, DIN 1946 Part 4, ÖNORM H 6021 and ÖNORM H 6020, SWKI VA 104-01 and SWKI 99-3, and EN 16798

## TECHNICAL INFORMATION

TECHNICAL DATA, SPECIFICATION TEXT, ORDER CODE, RELATED PRODUCTS



Fractional efficiency ePM10 [%] to ISO 16890	60	75	–	–	–
Fractional efficiency ePM2.5 [%] to ISO 16890	–	–	–	70	75
Fractional efficiency ePM1 [%] to ISO 16890	–	–	60	–	–
Initial differential pressure [Pa] at nominal volume flow rate	50	70	125	140	175
Recommended final differential pressure [Pa]	250 – 350	250 – 350	250 – 350	250 – 350	250 – 350
Max. operating temperature [°C] for frames made of plastic	60	60	60	60	60
Max. operating temperature [°C] for frames made of galvanised sheet steel	90	90	90	90	90

Pocket filters PFS made of non-woven synthetic fibres as prefilters or final filters for the separation of fine dust in ventilation systems. Filter pockets provide a high dust holding capacity at a low initial differential pressure. Pocket filters made of non-woven synthetic fibres are available in standard and special sizes; variable number of pockets and pocket depth; filter groups ISO ePM10, ISO ePM2.5 and ISO ePM1 according to ISO 16890. Pocket filters made of non-woven synthetic fibres are Eurovent-certified and compliant with VDI 6022 in terms of hygiene.

### Materials and surfaces

- Filter media made of non-woven synthetic fibres
- Frame made of plastic or galvanised sheet steel

### Construction

- PLA: Frame made of plastic
- GAL: Frame made of galvanised steel

### Materials and surfaces

- Filter media made of non-woven synthetic fibres
- Frame made of plastic or galvanised sheet steel

### Sizing data

- Filter group [ISO 16890]
- Efficiency [%]
- Volume flow rate [m³/h]
- Initial differential pressure [Pa]
- Nominal size [mm]

PFS	-	ePM1	-	60%	-	PLA	-	25	/	592 x 592 x 600	x	8
1		2		3		4		5		6		7

1 Type  
PFS Pocket filters made of non-woven synthetic fibres

2 Classification  
ePM10 Fractional efficiency ePM10 to ISO 16890  
ePM2.5 Fractional efficiency ePM2.5 to ISO 16890  
ePM1 Fractional efficiency ePM1 to ISO 16890

3 Efficiency [%]  
to ISO 16890

4 Construction  
PLA Frame made of plastic  
GAL Frame made of galvanised steel

5 Frame depth [mm]  
20 (Only with GAL)  
25

6 Nominal size [mm]  
B x H x T

7 Number of pockets

- 3
- 4
- 5
- 6
- 7
- 8


## DIMENSIONS



①			Number of pockets	Filter class	②		③	④	⑤
B [mm]	H [mm]	T [mm]			qv [l/s]	qv [m³/h]	ΔpA [Pa]	m²	kg
592	592	600	6	ePM10 60%	944	3400	50	4,4	1,5
490	592	600	5	ePM10 60%	778	2800	50	3,7	1,3
287	592	600	3	ePM10 60%	472	1700	50	2,2	0,9
592	490	600	6	ePM10 60%	778	2800	50	3,6	1,4
592	287	600	6	ePM10 60%	472	1700	50	2,1	0,9
287	287	600	3	ePM10 60%	236	850	50	1,1	0,5
592	892	600	6	ePM10 60%	1417	5100	50	6,6	2
490	892	600	5	ePM10 60%	1167	4200	50	5,5	1,6
287	892	600	3	ePM10 60%	708	2550	50	3,3	1,1
592	592	600	6	ePM10 75%	944	3400	70	4,4	1,5
490	592	600	5	ePM10 75%	778	2800	70	3,7	1,3
287	592	600	3	ePM10 75%	472	1700	70	2,2	0,9
592	490	600	6	ePM10 75%	778	2800	70	3,6	1,4
592	287	600	6	ePM10 75%	472	1700	70	2,1	0,9
287	287	600	3	ePM10 75%	236	850	70	1,1	0,5
592	892	600	6	ePM10 75%	1417	5100	70	6,6	2
490	892	600	5	ePM10 75%	1167	4200	70	5,5	1,6
287	892	600	3	ePM10 75%	708	2550	70	3,3	1,1
592	592	600	8	ePM1 60%	944	3400	125	5,9	2
490	592	600	7	ePM1 60%	778	2800	125	5,1	1,7
287	592	600	4	ePM1 60%	472	1700	125	2,9	1,1
592	490	600	8	ePM1 60%	778	2800	125	4,9	1,7
592	287	600	8	ePM1 60%	472	1700	125	2,8	1,1
287	287	600	4	ePM1 60%	236	850	125	1,4	0,6
592	892	600	8	ePM1 60%	1417	5100	125	8,8	2,4
490	892	600	7	ePM1 60%	1167	4200	125	7,7	2,2

①			Number of pockets	Filter class	②		③	④	⑤
B [mm]	H [mm]	T [mm]			qv [l/s]	qv [m³/h]	ΔpA [Pa]	m²	kg
287	892	600	4	ePM1 60%	708	2550	125	4,4	1,4
592	592	600	8	ePM2.5 70%	944	3400	140	5,9	2
490	592	600	7	ePM2.5 70%	778	2800	140	5,1	1,7
287	592	600	4	ePM2.5 70%	472	1700	140	2,9	1,1
592	490	600	8	ePM2.5 70%	778	2800	140	4,9	1,7
592	287	600	8	ePM2.5 70%	472	1700	140	2,8	1,1
287	287	600	4	ePM2.5 70%	236	850	140	1,4	0,6
592	892	600	8	ePM2.5 70%	1417	5100	140	8,8	2,4
490	892	600	7	ePM2.5 70%	1167	4200	140	7,7	2,2
287	892	600	4	ePM2.5 70%	708	2550	140	4,4	1,4
592	592	600	8	ePM2.5 75%	944	3400	175	5,9	2
490	592	600	7	ePM2.5 75%	778	2800	175	5,1	1,7
287	592	600	4	ePM2.5 75%	472	1700	175	2,9	1,1
592	490	600	8	ePM2.5 75%	778	2800	175	4,9	1,7
592	287	600	8	ePM2.5 75%	472	1700	175	2,8	1,1
287	287	600	4	ePM2.5 75%	236	850	175	1,4	0,6
592	892	600	8	ePM2.5 75%	1417	5100	175	8,8	2,4
490	892	600	7	ePM2.5 75%	1167	4200	175	7,7	2,2
287	892	600	4	ePM2.5 75%	708	2550	175	4,4	1,4

Dimensional drawing of PFS-...-PLA/...



TROX GmbH



Heinrich-Trox-Platz  
D-47504 Neukirchen-Vluyn  
Tel.: +49 (0)2845 202-0  
Fax: +49 (0)2845 202-265

myTROX Services

- › Order-Status

---

- › TROX Academy

---

- › Catalogue Download

---

- › Your contact partner

---

- › Online fault report

---

- › BIM

---

Service-Hotlines

Sales Germany  
and technical consulting  
+49 (0)2845 202-0  
[Contact](#)

Technical service  
+49 (0)2845 202-400  
[Contact](#)

TROX IN SOCIAL WEB