



## TYPE MD

[Configure now](#)

### FOR THE DISPLAY, MONITORING AND CONTROL OF DIFFERENTIAL PRESSURES

Measuring devices for the display, monitoring and control of differential pressures or volume flow rates, for gaseous, non-aggressive media

Analogue:

- U-tube manometer or inclined tube manometer

Digital:

- Transducer with pressure sensor
- 4-digit LCD
- Infinitely variable setpoint adjustment
- Optical signal when the setpoint is reached
- Volt-free switch output with changeover contact
- 0.1 Pa resolution
- Signal outputs to DIN IEC 60381

## APPLICATION

Application

- Type MD pressure measuring devices for installation into ventilation and air conditioning systems
- For the display and monitoring of differential pressures in gaseous media, such as air and inert gases
- To ensure the timely maintenance of filters

Special characteristics

- Compact construction
- Easy to use
- Variant APC: display of 2 measuring ranges depending on installation orientation
- Variant DPC: measurement to DIN 1946-4 and VDI 3803
- Variant DPC can be integrated with the central BMS

## DESCRIPTION

Variants

- UT: U-tube manometer
- APC: Analog pressure monitor
- DPC: Digital pressure monitor

Construction

- Analog constructions: U-tube manometer and inclined tube manometer with fluid
- Digital construction: with electronic system
- Supply voltage 24 V AC/DC  $\pm$  15%, 50/60 Hz
- Transducer output, adjustable, 0 – 10 V DC, 0 – 20 mA or 2 – 10 V DC, 4 – 20 mA

Useful additions

- Manometer liquid, to be ordered separately
- DIN rail power supply unit, to be ordered separately

## TECHNICAL INFORMATION

Type MD pressure measuring devices with different measuring ranges for displaying or monitoring the differential pressure of gaseous media.

U-tube manometer and analogue pressure monitor are measuring devices with display function.

The digital pressure monitor is a monitoring and measuring device with a digital display including LEDs; an optical signal is emitted if the differential pressure exceeds the set limit.


Volt-free switch output with changeover contact and transducer output, adjustable, 0 – 10 V DC, 0 – 20 mA or 2 – 10 V DC, 4 – 20 mA, for connection to the central BMS.

Special characteristics

- Compact construction
- Easy to use
- Variant APC: display of 2 measuring ranges depending on installation orientation
- Variant DPC: measurement to DIN 1946-4 and VDI 3803
- Variant DPC can be integrated with the central BMS

Construction

- Analogue constructions: U-tube manometer and inclined tube manometer with liquid
- Digital construction: with electronic system
- Supply voltage 24 V AC/DC ± 15%, 50/60 Hz
- Transducer output, adjustable, 0 – 10 V DC, 0 – 20 mA or 2 – 10 V DC, 4 – 20 mA



- 1** Type  
**MD** Measuring device
- 2** Variant  
**UT** U-tube manometer  
**APC** Analogue pressure monitor  
**DPC** Digital pressure monitor
- 3** Supply voltage  
**24** 24 V AC/DC ± 15%, 50/60Hz

TROX GmbH



Heinrich-Trox-Platz  
D-47504 Neukirchen-Vluyn  
Tel.: +49 (0)2845 202-0  
Fax: +49 (0)2845 202-265

myTROX Services

- > Order-Status
- > TROX Academy
- > Catalogue Download
- > Your contact partner
- > Online fault report
- > BIM

Service-Hotlines

Sales Germany  
and technical consulting  
+49 (0)2845 202-0  
[Contact](#)

Technical service  
+49 (0)2845 202-400  
[Contact](#)

TROX IN SOCIAL WEB