



TNC-EC-AZM DISPLAY **MODULE**



TNC-EC-AZM DISPLAY **MODULE**



LED/BUZZER **COMBINATION**

TNC-EC-AZM

SYSTEM FOR CONTROLLING AND MONITORING MOTORISED FIRE DAMPERS

Stand-alone solution for controlling and monitoring up to 12 motorised fire dampers or up to 24 damper blade end positions

- Easy electrical installation using coded plug connections
 Pre-installed application software
 No additional programming required
 Improves the fire safety

Application


Application


- Display module for menu-driven operation and error display
 2.8 inch colour LED and backlit function buttons with rocker switch for cursor allow for menu-driven operation and error display
 Language selection (German, English, Finnish; other languages upon request)

- Connecting cable for data and supply voltage, standard length of 5 m
- Menu-driven functional test
- Manual control of fire dampers
- Password protection

TECHNICAL INFORMATION

TNC-EC-AZM





Standard description (characteristics)

Menu-driven operation and display of the TNC-EASYCONTROL control system

- 2.8 inch colour LCD with 5 function buttons and rocker switch for cursor
- Language selection (for operation and display): German, English, Finnish
- CAN bus interface

- Supply voltage: 8 32 V DC
 Power consumption: 70 mA at 24 V DC
 Dimensions: 87.5 × 87.5 × 37.5 mm (B × H × T)
- Casing: plastic, black
 Protection level: IP 67 when installed in the front panel of the casing, otherwise IP 65
 Operating manual
 Make: TROX GmbH or equivalent
 Type: TNC-EC-AZM

TNC - EasyControl - Schaltnetzteil





TNC-EasyControl switching power supply unit