

FIRE DAMPER TYPE FKRS-EU - UPDATED DOCUMENTATION

[🕒 back to the
overview](#)

date **09.07.2020**
rubric **products**

For type FKRS-EU, the following updated documentation is available:

- > [Installation and operating manual FKRS-EU](#)
- > [Declaration of performance DoP / FKRS-EU / DE / 004](#)
- > [Product data sheet FKRS-EU](#)

The following special features are new:

- > **Perimeter gap** with mortar-based installation: now up to 225 mm
- > **Combined installation:** fire dampers of type FKRS-EU may be installed together with fire dampers of types FK-EU or FK2-EU in the same installation opening in solid walls, lightweight partition walls and shaft walls with metal support structure and in a concrete base
- > **Multiple assignment:** up to 10 fire dampers may be installed side by side or one below the other in installation openings of $\leq 1.2 \text{ m}^2$ in solid walls and in a concrete base

[Click here to configure and shop online the FKRS-EU fire damper.](#)

TROX GmbH



Heinrich-Trox-Platz
D-47504 Neukirchen-Vluyn
Tel.: +49 (0)2845 202-0
Fax: +49 (0)2845 202-265

myTROX Services

- > [Order-Status](#)
- > [TROX Academy](#)
- > [Catalogue Download](#)
- > [Your contact partner](#)
- > [Online fault report](#)
- > [BIM](#)

Service-Hotlines

Sales Germany
and technical consulting
+49 (0)2845 202-0
[Contact](#)

Technical service
+49 (0)2845 202-400
[Contact](#)

TROX IN SOCIAL WEB