

...



TNC-A4000



TNC-A4000

## TNC-A4000

AS-I FLAT CABLE FOR USE WITH FLAT CABLE INSULATION DISPLACEMENT CONNECTORS AND COMPACT MODULES, AVAILABLE AS A ROLL OF 25 M, 50 M OR 100 M

All products are of high quality and meet the requirements of AS-Interface

- Asymmetrically shaped cable to ensure error-free connection (reverse voltage protection)
- Easy wiring due to flat cable insulation displacement connectors ('click and go')
- Protection level up to IP 67



TNC-70413



TNC-70113



TNC-DP CONNECTOR



## Application


### Application

- AS-i flat cable for the transmission of data (communication) and voltage to the slaves
- For use with flat cable connectors and mounting bases

## TECHNICAL INFORMATION

AS-i installation TNC-A4000

...



- ① bl ⊖  
② bn ⊕

Description	TNC-A4000
Temperature range	-40 to 85 °C
Material	EPR (ethylene propylene); free of halogens
Colour	Traffic yellow
Protection level	IP 67 in connection with flat cable mounting base
Wire diameter	2 × 1.5 mm <sup>2</sup>
Wire colours	Brown (AS-i +), blue (AS-i -)
Special features	Reverse voltage protection due to special shape
Available lengths	50 or 100 m

#### Standard description (characteristics)

AS-i flat cable for use with flat cable insulation displacement connectors and Compact modules, available as a roll of 50 m or 100 m

- Supply voltage: 26.5 – 31.6 V DC (AS-i)
- Electrical design: AS-i
- Connection: 2 × 1.5 mm<sup>2</sup>
- Ambient temperature: -40 to 85 C°
- Protection level: IP 67
- Make: TROX GmbH or equivalent
- Type: TNC-A4000

...

# TNC – A4000



## **1** Useful additions

**TNC-A4000** Flat cable (100 m)  
**TNC-70381** Flat cable distributor  
**TNC-70413** End seals (10 pieces)  
**TNC-70113** Heat shrink caps (10 pieces)  
**TNC-70067** Cable clips for flat cables (100 pieces)  
**TNC-DP connector**

## TROX GmbH



Heinrich-Trox-Platz  
D-47504 Neukirchen-Vluyn  
Tel.: +49 (0)2845 202-0  
Fax: +49 (0)2845 202-265

## myTROX Services

- > Order-Status
- > TROX Academy
- > Catalogue Download
- > Your contact partner
- > Online fault report
- > BIM

## Service-Hotlines

Sales Germany  
and technical consulting  
+49 (0)2845 202-0  
[Contact](#)

Technical service  
+49 (0)2845 202-400  
[Contact](#)

## TROX IN SOCIAL WEB