

...



TNC-A1305



TNC-A1305

AS-I CONTROLLER WITH 1 MASTER IS A COMPACT AS-I MASTER SYSTEM WITH INTEGRAL TEXT/GRAPHIC DISPLAY AND PROFIBUS DP INTERFACE.

Controller for controlling actuators and for monitoring the damper blade position and duct smoke detectors

- Controller with TROXNETCOM Basic User Software
- Easy and safe commissioning without programming
- Controller with master function for stand-alone operation
- System monitoring
- Automatic recognition of components and their status
- Menu-driven user interface (controller display) for system configuration
- Peripheral equipment can be tested without additional auxiliary equipment

Application




Application

- AS-i controller TNC-A1305 with 1 master for 31 AS-i slaves
- Decentralised operating and monitoring system with signal preprocessing and gateway
- With TNC Basic User Software
- Recognition of all slaves on a bus
- For initialising the AS interface network
- Error diagnosis and signalling
- LC display, 43 × 28 mm, also for operation
- PROFIBUS DP interface

TECHNICAL INFORMATION

AS-i controller TNC-A1305



...

Description	TNC-A1305
Supply voltage	24 V DC
Current consumption	< 500 mA
Power consumption	< 10 VA
Programming interface	RS232C: RJ11; 9600 – 115200 Bd, galvanically isolated
Data interface	PROFIBUS DP (EN 50170); max. 12 MBd slave
Diagnosis via PROFIBUS DP	Yes
PLC memory for user program	128 Kwords
Display	Graphic LC display 128 × 64 pixels, 43 × 28 mm
Max. acceptable rel. humidity	< 95 %
Status LED	2 × red; 2 × green; 2 × yellow
Ambient temperature	0 to 60 °C
Storage temperature	–20 to 70 °C
Protection level	IP 20
MTTF	5 years
AS-i profile	M3
AS-i certificate	61103
Casing materials	Aluminium, galvanised sheet steel
Casing dimensions	124 × 97 × 86 mm
Fixing	On DIN mounting rail

Standard description (characteristics)

AS-i controller TNC-A1305 (1 master) is a compact AS-i master system with integral text/graphic display and PROFIBUS DP interface.

- Control of components as part of fire damper control

Integral TNC Basic User Software with the following functions:

- Automatic recognition of TROX modules and their functions
 - Automatic grouping
 - Network control
 - Automatic functional test
 - Manual control of dampers
 - Integral display, also for operation
 - Simple, menu-driven configuration and adjustment
-
- Supply voltage: 24 V DC
 - Total current consumption from AS-i: < 10 mA
 - Casing materials: Aluminium, galvanised sheet steel
 - Ambient temperature: 0 – 60 °C
 - Protection level: IP 20
 - Status display: LEDs, 2 x red, 2 x green, 2 x yellow
 - Make: TROX GmbH or equivalent
 - Type: TNC-A1305

...

TNC – A1305



1 Component

TNC-A1305	Controller with PROFIBUS DP interface; 1 master
TNC-A1306	Controller with PROFIBUS DP interface; 2 masters
TNC-A1353	Controller with Modbus/TCP interface; 1 master
TNC-A1354	Controller with Modbus/TCP interface; 2 masters
TNC-A1375	Gateway with PROFIBUS DP interface; 1 master
TNC-A2225	Repeater
TNC-ZB0252	AS-i safety gateway
TNC-Z0119	Passive bus termination
TNC-A1146	AS-i tuner (diagnosis module)

TROX GmbH



Heinrich-Trox-Platz
D-47504 Neukirchen-Vluyn
Tel.: +49 (0)2845 202-0
Fax: +49 (0)2845 202-265

myTROX Services

- › Order-Status
- › TROX Academy
- › Catalogue Download
- › Your contact partner
- › Online fault report
- › BIM

Service-Hotlines

Sales Germany
and technical consulting
+49 (0)2845 202-0
[Contact](#)

Technical service
+49 (0)2845 202-400
[Contact](#)

TROX IN SOCIAL WEB