

...



{249}

TNC-D1030

SWITCHING POWER SUPPLY UNIT FOR 24 V SUPPLY

Controlled power supply for sensors, actuators, sensor electronics and controller

- High efficiency of > 84 %
- Input and output with overvoltage protection
- Can be attached to a mounting rail, no tools required
- Output voltage adjustable up to 28 V DC
- Overload protection, up to 1.5 × nominal current
- Very high efficiency, hence very low heat buildup
- LED for secondary voltage

General Information



Application

- Switching power supply unit TNC-D1030 (24 V DC; 1.25 A)
- Power supply for AS-i controllers as well as for operating and display units
- Very high efficiency of 84 %
- Low ripple voltage 50 mV
- High reliability

TECHNICAL INFORMATION

Specification Text, Order Code



Specification text

- Switching power supply unit for supplying the controller or text display with power
- Nominal voltage: < 230 V AC
- Output voltage: 24 – 28 V DC ($\pm 2\%$), SELV/PELV
- Output current: 1.25 A
- Nominal frequency: 47 – 63 Hz
- Efficiency: 84 % (230 V AC; 24 V DC/1.25 A)
- Connection: spring cage terminals
- Casing materials: PC-ABS
- Ambient temperature: 0 – 70 °C
- Protection level: IP 20
- Status display: LED green
- Make: TROX GmbH or equivalent

...

TNC

-
|
1

D1030

1 Type

TNC-D1030 Output current 1.25 A

TNC-D4011 Output current 3.3 A

TNC-D4012 Output current 5 A

TNC-D4013 Output current 10 A

TECHNICAL DATA



Description	TNC-D1030
Output current	1.25 A
Nominal voltage	< 230 V AC
Input voltage range	100 – 240 V AC
Nominal frequency	47 – 63 Hz
Efficiency	84 %
TROX casing	PC-ABS
Protection level	IP 20
IEC protection class	II (protective earth)
Connection	Spring cage terminals
Temperature range	0 – 70 °C
Derating	2 %/K (> 60 °C)
Output voltage	24 – 28 V DC (± 2 %) to SELV/PELV
Readiness delay time	< 255 s
Max. ripple voltage	50 mV
Mains buffering time	120 ms
Short-circuit protection / overload protection	Yes (to IEC 61140)
EMC	EN 61000-6-2; EN 61000-6-3
LEDs	DC OK; 1 x LED, green
Weight	278.5 g
Dimensions	90 x 45 x 100 mm

...

